

## Roulement conique 835R-832-JTEKT - 835R-832-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/835r-832-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> <sub>min.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
69.850	168.275	53.975	56.383	41.275	3.6	3.2	344	467	2 300	3 100

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> <sub>max.</sub>	<i>r</i> <sub>b</sub> <sub>max.</sub>	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
835R	832	35.0	91.0	84.0	149.0	155.0	3.6	3.2	0.30	2.00	1.10	4.32	1.72

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428871
Diam. intérieur	69.85 mm
Diam. extérieur	168.275 mm
Épaisseur	53.975 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE