

## Roulement conique 47681R-47620-JTEKT - 47681R-47620-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/47681r-47620-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
80.962	133.350	33.338	33.338	26.195	3.6	3.2	154	245	2 700	3 700

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
47681R	47620	29.2	95.0	89.0	119.0	128.0	3.6	3.2	0.40	1.48	0.82	1.17	0.577

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429304
Diam. intérieur	80.962 mm
Diam. intérieur	3 3/16" inch
Diam. extérieur	133.35 mm
Diam. extérieur	5 1/4" inch
Epaisseur	33.338 mm
Epaisseur	1 5/16" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE