


## Roulement conique 778-772-JTEKT - 778-772-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/778-772-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_{\text{max}}$	$r_{\text{min}}$	$C_r$	$C_{10}$	Grease lub.	Oil lub.
92.075	180.975	47.625	48.006	38.100	3.6	3.2	288	438	2 100	2 800

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)						Constant $e$	Axial load factors		(Refer to)	
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.		$Y_1$	$Y_2$	Inner ring	Outer ring
778	772	39.5	111.0	105.0	161.0	168.0	3.6	3.2	0.39	1.56	0.86	3.65	1.92

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429779
Diam. intérieur	92.075 mm
Diam. extérieur	180.975 mm
Épaisseur	47.625 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE