


## Roulement conique 787-772-JTEKT - 787-772-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/787-772-jtekt>

Single-row tapered roller bearings  
inch series



**Koyo**

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> <sub>min.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
104.775	180.975	47.625	48.006	38.100	7.1	3.2	288	438	2 100	2 800

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)					Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> <sub>max.</sub>		<i>r</i> <sub>b</sub> <sub>max.</sub>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
787	772	39.5	129.0	116.0	161.0	168.0	7.1	3.2	0.39	1.56	0.86	2.87	1.92

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430034
Diam. intérieur	104.775 mm
Diam. extérieur	180.975 mm
Épaisseur	47.625 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE