

Roulement conique 936-932-JTEKT - 936-932-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/936-932-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ _{min.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 107.950 | 212.725 | 66.675 | 66.675 | 53.975 | 7.9 | 3.2 | 450 | 674 | 1 800 | 2 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|--------------------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a _{max.} | <i>r</i> _b _{max.} | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 936 | 932 | 47.6 | 137.0 | 122.0 | 167.0 | 193.0 | 7.9 | 3.2 | 0.33 | 1.84 | 1.01 | 6.52 | 4.07 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952430126 |
| Diam. intérieur | 107.95 mm |
| Diam. extérieur | 212.725 mm |
| Épaisseur | 66.675 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE