

Roulement conique L540049-L540010-JTEKT - L540049-L540010-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/l540049-l540010-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|------------------|------------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_{max} | r_{min} | C_r | C_{10} | Grease lub. | Oil lub. |
| 196.850 | 254.000 | 28.575 | 27.783 | 21.433 | 1.6 | 1.6 | 188 | 387 | 1 200 | 1 600 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|------------|------------|----------|--------------------|-------|--------------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| L540049 | L540010 | 43.1 | 206.0 | 214.0 | 238.0 | 243.0 | 1.6 | 1.6 | 0.40 | 1.51 | 0.83 | 2.34 | 1.02 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952431772 |
| Diam. intérieur | 196.85 mm |
| Diam. extérieur | 254 mm |
| Épaisseur | 28.575 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE