


Roulement à aiguilles 15MM2112-JTEKT - 15MM2112-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/15mm2112-jtekt>

Drawn cup needle roller bearings 

Full complement type
With closed end



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---------------------------|
| F_w | D | C | b min. | C_0 | C_{10} | Oil lub. |
| 15 | 21 | 12 | 9.6 | 9.70 | 15.9 | 8 100 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| | 15MM2112 | 14.989 | 15.000 | 20.972 | 20.993 | 12 | 13 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470108 |
| Diam. intérieur | 15 mm |
| Diam. intérieur | 0.591" inch |
| Diam. extérieur | 21 mm |
| Diam. extérieur | 0.827" inch |
| Epaisseur | 12 mm |
| Epaisseur | 0.472" inch |
| Poids | 13 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE