

## Roulement à aiguilles 16BTM2216-JTEKT - 16BTM2216-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/16btm2216-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type With open ends    With closed end
16	22	16	13.3	10.7	15.1	22 000	<b>16BTM2216</b>

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.972	21.993	15	17

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250088742
Diam. intérieur	16 mm
Diam. intérieur	0.63" inch
Diam. extérieur	22 mm
Diam. extérieur	0.866" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Poids	15 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE