

Roulement à aiguilles BTM172425-JTEKT - BTM172425-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/btm172425-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 17 | 24 | 25 | — | 19.0 | 29.0 | 20 000 | BTM172425 | |

| Full complement type | | Recommended dimensions (mm) | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|-----------------------------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | Housing bore dia. (N7) max. | With open ends | With closed end |
| — | — | 16.983 ²⁾ | 16.994 ²⁾ | 23.972 | 23.993 |
| | | | | 22 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470542 |
| Diam. intérieur | 17 mm |
| Diam. extérieur | 24 mm |
| Épaisseur | 25 mm |
| Poids | 22 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE