

## Roulement à aiguilles 20MKM2616-JTEKT - 20MKM2616-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/20mkm2616-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_r$	Oil lub.	Caged type With open ends    With closed end	
20	26	16	13.3	12.4	20.3	18 000	<b>20MKM2616</b>

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	19.987	20.000	25.972	25.993	19	21

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470856
Diam. intérieur	20 mm
Diam. extérieur	26 mm
Épaisseur	16 mm
Poids	21 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE