


Roulement à aiguilles 20BTM2620A-JTEKT - 20BTM2620A-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/20btm2620a-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|---------------------------|------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | |
| 20 | 26 | 20 | — | 15.2 | 26.4 | 18 000 | 20BTM2620A |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 19.987 | 20.000 | 25.972 | 25.993 | 24 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470887 |
| Diam. intérieur | 20 mm |
| Diam. extérieur | 26 mm |
| Épaisseur | 20 mm |
| Poids | 24 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE