

Roulement à aiguilles BTM2212-JTEKT - BTM2212-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/btm2212-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|-------------------------|-----------------|--------------------------------------|----------------------------------------------|
| F _w | D | C | C _r | C _{0r} | Oil lub. | Caged type With open ends With closed end |
| 22 | 29 | 12 | 9.22 | 13.0 | 16 000 | BTM2212 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 21.987 | 22.000 | 28.972 | 28.993 | 19 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952471181 |
| Diam. intérieur | 22 mm |
| Diam. extérieur | 29 mm |
| Épaisseur | 12 mm |
| Poids | 19 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE