

## Roulement à aiguilles BTM2220A-JTEKT - BTM2220A-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/btm2220a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{10}$	Oil lub.
22	29	20	17.3	18.2	26.7	16 000
						Caged type With open ends    With closed end <b>BTM2220A</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	30	33

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250004117
Diam. intérieur	22 mm
Diam. extérieur	29 mm
Épaisseur	20 mm
Poids	30 g
Conditionnement	-

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE