

## Roulement à aiguilles MHKM2820-JTEKT - MHKM2820-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/mhkm2820-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) |     |     | Basic load ratings (kN) |       | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                    |          |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|--|----------|
| $F_w$                    | $D$ | $C$ | $b$<br>min.             | $C_r$ | Oil lub.                             | Caged type<br>With open ends With closed end |          |
| 28                       | 37  | 20  | 17.3                    | 21.6  | 33.0                                 | 13 000                                       | MHKM2820 |

  

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | Refer. Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends       | With closed end | Shaft dia. (H6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends  | With closed end |
| —                    | —               | 27.987                      | 28.000 | 36.967                         | 36.992 | 46              | 52              |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952471747 |
| Diam. intérieur | 28 mm         |
| Diam. extérieur | 37 mm         |
| Épaisseur       | 20 mm         |
| Poids           | 52 g          |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE