

## Roulement à aiguilles BTM424709AJ-JTEKT - BTM424709AJ-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/btm424709aj-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) |       |      | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                       |
|--------------------------|-------|------|-------------------------|----------|--------------------------------------|---|
| $F_w$                    | $D$   | $C$  | $C_r$                   | $C_{0r}$ | Oil lub.                             | Caged type<br>With open ends    With closed end |
| 41.50                    | 46.50 | 8.50 | 7.00                    | 13.9     | 9 200                                | <b>BTM424709AJ</b>                              |

| Full complement type |                 | Recommended dimensions (mm) |        |                             |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6) min.        | max.   | Housing bore dia. (N7) min. | max.   | With open ends    | With closed end |
| —                    | —               | 41.484                      | 41.500 | 46.467                      | 46.492 | 15                | —               |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952472690 |
| Diam. intérieur | 41.5 mm       |
| Diam. extérieur | 46.5 mm       |
| Épaisseur       | 8.5 mm        |
| Poids           | 15 g          |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE