


Roulement à aiguilles MKM4520-JTEKT - MKM4520-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/mkm4520-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|------------------------------|-----------------|
| F_w | D | C | b min. | C_r | Oil lub. | Caged type With open ends | With closed end |
| 45 | 52 | 20 | 17.3 | 23.3 | 33.4 | 8 200 | MKM4520 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 44.984 | 45.000 | 54.961 | 54.991 | 79 | 90 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952472805 |
| Diam. intérieur | 45 mm |
| Diam. extérieur | 52 mm |
| Épaisseur | 20 mm |
| Poids | 90 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE