


## Roulement à aiguilles BTM5030-JTEKT - BTM5030-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/btm5030-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{10}$	Oil lub.	
50	62	30	27.3	52.8	98.5	7 300	BTM5030

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	49.984	50.000	61.961	61.991	153	173

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952472973
Diam. intérieur	50 mm
Diam. extérieur	62 mm
Épaisseur	30 mm
Poids	153 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE