


Roulement à rouleaux NN3015-JTEKT - NN3015-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nn3015-jtekt>

Double-row cylindrical roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | | Bearing No. | |
|--------------------------|-----|----|-------------------------|-------|----------|--------------------------------------|----------|------------------|--------------|
| d | D | B | F_w | C_r | C_{0r} | Grease lub. | Oil lub. | Cylindrical bore | Tapered bore |
| 75 | 115 | 30 | 105 | 99.0 | 155 | 5 200 | 6 200 | NN3015 | |

| | | Mounting dimensions (mm) | | | | | | (Refer.) Mass (kg) | |
|------------------|--------------|--------------------------|------|-------|-------|-------|------|--------------------|--------------|
| Cylindrical bore | Tapered bore | d_a | | D_a | | r_a | | Cylindrical bore | Tapered bore |
| | | min. | max. | min. | max. | min. | max. | | |
| | | 81.5 | — | — | 108.5 | 106 | 1 | 1.11 | 1.08 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952473727 |
| Diam. intérieur | 75 mm |
| Diam. extérieur | 115 mm |
| Épaisseur | 30 mm |
| Poids | 1110 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE