


## Roulement à aiguilles NA4900UU-JTEKT - NA4900UU-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na4900uu-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>w</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Without inner ring	
14	10	22	13	14	7.5	7.7	14 000	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With outer ring		d <sub>2</sub> min.	D <sub>2</sub> max.	r <sub>2</sub> max.	Without inner ring	With inner ring			
NA4900UU		12	20	0.3	—	0.025	IRM101414		

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477770
Diam. intérieur	10 mm
Diam. extérieur	22 mm
Épaisseur	13 mm
Poids	25 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE