


## Roulement à aiguilles NA6901-JTEKT - NA6901-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/na6901-jtekt>

Machined ring needle roller bearings ————— Koyo  
F<sub>w</sub> 29 – 37 mm

With inner ring



| Boundary dimensions (mm) |    |    |    | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|--|--------------------|-------------|
| F <sub>w</sub>           | d  | D  | B  | C <sub>r</sub>          | C <sub>10</sub> | Oil lub.   | Without inner ring |             |
| 16                       | 12 | 24 | 22 | —                       | 16.3            | 21.7   | 27 000             | —           |
| Mounting dimensions (mm) |    |    |    | (Refer.) Mass (kg)      |                 | (Refer.) Applicable inner ring No.                 |                    |             |
| With inner ring          |    |    |    | Without inner ring      | With inner ring | No.  |                    |             |
| NA6901                   |    |    |    | 14                      | 22              | 0.030  | 0.045              | IRM121622   |

[Note] 1) Limiting speeds of bearing number NA49...LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952477848 |
| Diam. intérieur | 12 mm         |
| Diam. extérieur | 24 mm         |
| Épaisseur       | 22 mm         |
| Poids           | 45 g          |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE