


Roulement à rouleaux NQ25-16-JTEKT - NQ25-16-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq25-16-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
25	—	33	16	—	14.1	20.6	18 000	NQ25/16
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _i min.	D _i max.	r _a max.	Without inner ring	With inner ring		
		—	31	0.3	0.034	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482354
Diam. intérieur	25 mm
Diam. extérieur	33 mm
Épaisseur	16 mm
Poids	34 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE