


## Roulement à rouleaux NA6904-JTEKT - NA6904-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/na6904-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
25	20	37	30	35.4	48.9	17 000	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
NA6904				22	35	0.096	0.137	IRM202530

[Note] 1) Limiting speeds of bearing number NA49..LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482453
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	30 mm
Poids	137 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE