


Roulement à rouleaux NQ26-16-JTEKT - NQ26-16-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq26-16-jtekt>

Machined ring needle roller bearings ————— Koyo
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
26	22	34	16	14.1	24.2	18 000	NQ26/16	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
d _a min.	D _a max.	r _a max.	0.3	0.037	0.056			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482460
Diam. intérieur	26 mm
Diam. extérieur	34 mm
Épaisseur	16 mm
Poids	37 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE