


Roulement à rouleaux NQI22-16-JTEKT - NQI22-16-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nqi22-16-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|----|----|----------|-------------------------|-----------------|--|-------|--------------------|---|
| F_w | d | D | B | B_{10} | C_r | C_{10} | Oil lub. | | Without inner ring | |
| 26 | 22 | 34 | 16 | — | 14.1 | 24.2 | 18 000 | | — | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NQI22/16 | | | | | 24 | 32 | 0.3 | 0.037 | 0.056 | — |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952482477 |
| Diam. intérieur | 22 mm |
| Diam. extérieur | 34 mm |
| Épaisseur | 16 mm |
| Poids | 56 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE