

## Roulement à rouleaux NQ28-30-JTEKT - NQ28-30-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq28-30-jtekt>

### Machined ring needle roller bearings

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	$d$	$D$	$B$	$B_r$	$C_r$	$C_{10}$	Oil lub.		Without inner ring	
28	—	37	30	—	0.3	29.1	54.1	16 000		NQ28/30
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring				
		max.	max.	max.	—	—				
		—	35	0.3	0.083	—				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482521
Diam. intérieur	28 mm
Diam. intérieur	1.102" inch
Diam. extérieur	37 mm
Diam. extérieur	1.457" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Poids	83 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE