


Roulement à rouleaux NQ30-20-JTEKT - NQ30-20-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq30-20-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
30	—	40	20	23.7	37.5	15 000	NQ30/20	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _a	D _a	r _a	0.066	—			
	max.	max.	max.					
	—	38	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482644
Diam. intérieur	30 mm
Diam. extérieur	40 mm
Épaisseur	20 mm
Poids	66 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE