


Roulement à rouleaux NQ32-20-JTEKT - NQ32-20-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq32-20-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	B_i	r mm	C_r	C_{10}	Oil lub.	Without inner ring
32	28	42	20	—	0.3	24.3	39.4	14 000	NQ32/20
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring		d_i min.	D_i max.	r_i max.	Without inner ring	With inner ring			
		30	40	0.3	0.070	0.098			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482774
Diam. intérieur	32 mm
Diam. extérieur	42 mm
Épaisseur	20 mm
Poids	70 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE