

Roulement à rouleaux NQS32-22-JTEKT - NQS32-22-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nqs32-22-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
32	25	47	22	31.2	41.4	14 000	NQS32/22	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d_a	D_a	r_a	0.123	0.167			
	min.	max.	max.					
	27	45	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482835
Diam. intérieur	32 mm
Diam. extérieur	47 mm
Épaisseur	22 mm
Poids	123 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE