


## Roulement à aiguilles NQI30-20-JTEKT - NQI30-20-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/aiguilles/nqi30-20-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.		Without inner ring
35	30	45	20	—	24.7	41.4	13 000		—
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring					Without inner ring	With inner ring			
	d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>						
	max.	max.	max.						
	NQI30/20	32	43	0.3		0.108			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482866
Diam. intérieur	30 mm
Diam. extérieur	45 mm
Épaisseur	20 mm
Poids	108 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE