


Roulement à rouleaux NA4906UU-JTEKT - NA4906UU-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/na4906uu-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
35	30	47	17	19.5	25.3	5 700	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With upper ring		d_a	D_a	r_a	Without inner ring	With inner ring		
NA4906UU		32	45	0.3	—	0.105	IRM303518	

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482873
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	17 mm
Poids	105 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE