

## Roulement à rouleaux 40NQ5230-JTEKT - 40NQ5230-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/40nq5230-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
40	—	52	30	47.0	81.0	11 000	40NQ5230	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d <sub>a</sub>	D <sub>2</sub>	r <sub>a</sub>	—	0.148	—		
	max.	max.	max.					
	—	48	0.6					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483085
Diam. intérieur	40 mm
Diam. extérieur	52 mm
Épaisseur	30 mm
Poids	148 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE