


Roulement à rouleaux NQI38-30-JTEKT - NQI38-30-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nqi38-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	B_1	r_{min}	C_r	C_{10}	Oil lub.	Without inner ring
43	38	53	30	30	0.6	41.3	85.9	10 000	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring		d_a	D_a	r_a	Without inner ring	With inner ring			
NQI38/30		—	51	0.6	—	0.205			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483191
Diam. intérieur	38 mm
Diam. extérieur	53 mm
Épaisseur	30 mm
Poids	205 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE