

Roulement à rouleaux NQ506525-JTEKT - NQ506525-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq506525-jtekt>

Machined ring needle roller bearings ————— Koyo
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
50	—	65	25	48.3	77.8	9 100	NQ506525	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
—	d _a min.	D _a max.	r _a max.	0.6	0.190	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483375
Diam. intérieur	50 mm
Diam. extérieur	65 mm
Épaisseur	25 mm
Poids	190 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE