


Roulement à rouleaux 55NQ6720A-JTEKT - 55NQ6720A-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/55nq6720a-jtekt>

Machined ring needle roller bearings ————— Koyo
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
55	—	67	20	—	24.1	46.2	8 900	55NQ6720A
		Mounting dimensions (mm)			(roller) Mass (kg)		(roller) Applicable inner ring No.	
With inner ring		d _i min.	D _i max.	r _a max.	Without inner ring	With inner ring		
		—	63	0.6	0.136	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483467
Diam. intérieur	55 mm
Diam. extérieur	67 mm
Épaisseur	20 mm
Poids	136 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE