

Roulement à rouleaux RNA4920-JTEKT - RNA4920-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/rna4920-jtekt>

Machined ring needle roller bearings ————— Koyo
F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 115 | 100 | 140 | 40 | 144.0 | 296.0 | 4 000 | RNA4920 | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| | d ₁ | D ₁ | r ₁ | 1 | 1.160 | 1.36 | IRM10011540 | |
| | max. | max. | max. | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952484211 |
| Diam. intérieur | 115 mm |
| Diam. extérieur | 140 mm |
| Épaisseur | 40 mm |
| Poids | 1160 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE