


## Douille à aiguilles BAM1010-IKO - BAM1010-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam1010-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	BAM 1010	12	—	—	
Boundary dimensions mm (inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
$F_w$	$D$	$C$	$b_2$	Shaft dia. h8	Housing bore dia. J7	$C$	$C_0$	rpm		
15.875 ( $\frac{5}{8}$ )	20.638 ( $\frac{3}{4}$ )	15.881 (.625)	1.3	15.875 Max. Min.	15.884 Max. Min.	20.650 / 20.629	7 320	10 700	25 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172897
Diam. intérieur	15.88 mm
Diam. extérieur	20.64 mm
Épaisseur	15.88 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE