


Douille à aiguilles BAM1014-IKO - BAM1014-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam1014-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 ($\frac{5}{8}$)	—	—	—	—	—	BAM 1014	16.2	—	—	
Boundary dimensions mm (inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	N	N	rpm
15.875 $\frac{1}{4}$	20.638 $\frac{3}{4}$	22.22 $\frac{7}{8}$	1.3	15.875 Max.	15.864 Min.	20.650 Max.	20.629 Min.	10 700	17 500	25 000
IRB 714										

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172910
Diam. intérieur	15.88 mm
Diam. extérieur	20.64 mm
Épaisseur	22.22 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE