


Douille à aiguilles BAM118-IKO - BAM118-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam118-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
17.462 ($\frac{11}{16}$)	—	—	—	—	—	BAM 118	10.8	—	—
Boundary dimensions mm (inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	b_2	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm	
17.462 ($\frac{11}{16}$)	22.225 ($\frac{7}{8}$)	12.700 (.500)	1.3	17.462 17.451 22.237 22.216		6 140	8 850	25 000	IRB 88

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172996
Diam. intérieur	17.46 mm
Diam. extérieur	22.23 mm
Épaisseur	12.7 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE