


Douille à aiguilles BAM1216-IKO - BAM1216-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam1216-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
19.050 ($\frac{3}{4}$)	—	—	—	—	—	—	BAM 1216			28.5	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	r_2	Shaft dia. h_6	Housing bore dia. J_7	C	C_0	C_0	C_0	rpm	IRB 816-1		
Max.	Max.	Min.	Max.	Max.	Min.	N	N	N	N	rpm			
19.050	25.400	25.400	1.3	19.050	19.037	25.412	25.391	16 300	26 500	20 000			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173030
Diam. intérieur	19.05 mm
Diam. extérieur	25.4 mm
Épaisseur	25.4 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE