


Douille à aiguilles BAM1310-IKO - BAM1310-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam1310-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number																
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g								
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	BAM 1310	20	—								
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	r_2	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	rpm					
20.638	26.988	15.881	1.3	20.638	20.625	27.000	26.979	9 870	14 200	19 000	IRB 910						

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173061
Diam. intérieur	20.64 mm
Diam. extérieur	26.99 mm
Épaisseur	15.88 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE