


Douille à aiguilles BAM136-IKO - BAM136-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam136-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
20.638 ($\frac{3}{4}$)	—	—	—	—	—	—	BAM 136	12.6	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>r₂</i> Max.	Shaft dia. <i>h6</i> Max. Min.	Housing bore dia. <i>J7</i> Max. Min.	N	N	rpm	
20.638 $\frac{3}{4}$	26.988 $1\frac{1}{8}$	9.521 $\frac{3}{8}$	1.3	20.638 20.625 27.000 26.979	5 230	6 300	19 000	—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173115
Diam. intérieur	20.64 mm
Diam. extérieur	26.99 mm
Épaisseur	9.52 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE