


Douille à aiguilles BAM148-IKO - BAM148-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam148-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
22.225 (7/8)	—	—	—	—	—	BAM 148	17.8	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	r ₂ Max.	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm	IRB 108
22.225 7/8	28.575 1 1/8	12.70 .500	2.8	22.225 22.212	28.587 28.566	7 440	10 100	18 000	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173191
Diam. intérieur	22.23 mm
Diam. intérieur	7/8" inch
Diam. extérieur	28.58 mm
Diam. extérieur	1 1/8" inch
Epaisseur	12.7 mm
Epaisseur	1/2" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE