


## Douille à aiguilles BAM166-IKO - BAM166-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam166-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
25.400 (1)	—	—	—	—	—	<b>BAM 166</b>	16	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $\phi_s$	Housing bore dia. $\phi_H$	$J_7$	$C$	$C_0$	rpm		
Max.	Max.	Max.	Max.	Min.	Max.	Min.	N	N		
25.400	31.750	9.52	25.400	25.387	31.764	31.739	6 010	8 020	15 000	—

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173283
Diam. intérieur	25.4 mm
Diam. extérieur	31.75 mm
Épaisseur	9.52 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE