

Douille à aiguilles BAM1716-IKO - BAM1716-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam1716-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g			
26.988 (1 1/8)	—	—	—	—	—	—	—	BAM 1716	40.5	—	—	
Boundary dimensions mm (inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F_w	D	C	t_1 Max	Shaft dia. h8 Max	Housing bore dia. H7 Max	Min	Max	Min	N	N	rpm	—
26.988 (1 1/8)	33.338 (1 1/4)	25.40 (1.000)	2.8	26.988	26.975	33.352	33.327	20 000	38 900	14 000	—	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173320
Diam. intérieur	26.99 mm
Diam. extérieur	33.34 mm
Épaisseur	25.4 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE