


Douille à aiguilles BAM56-IKO - BAM56-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam56-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
7.938 ($\frac{5}{16}$)	—	—	—	—	—	—	—	BAM 56	3.9	—	—
Boundary dimensions mm (inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F _w	D	C	b ₂ Max.	h ₈ Max.	Housing bore dia. J7 Min.	N	N	rpm			
7.938	12.700	9.521	1	7.938	7.929	12.710	12.692	2 620	2 390	45 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173443
Diam. intérieur	7.94 mm
Diam. extérieur	12.7 mm
Épaisseur	9.52 mm
Poids	3.9 g
Conditionnement	-
Norme	Sans norme

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE