


Douille à aiguilles BAM710-IKO - BAM710-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam710-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g			
11.112 ($\frac{7}{16}$)	—	—	—	—	—	—	—	BAM 710	8.5	—		
Boundary dimensions mm (inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring				
F_w	D	C	h_1 Max.	h_2 Max.	Shaft dia. h_8 Min.	Housing bore dia. J Min.	N	C_0	N	rpm		
11.112 ($\frac{7}{16}$)	15.875 ($\frac{5}{8}$)	15.88 (0.625)	1	1	11.112	11.101	15.885	15.887	6 020	7 550	35 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173528
Diam. intérieur	11.11 mm
Diam. extérieur	15.88 mm
Épaisseur	15.88 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE