


Douille à aiguilles BAM810-IKO - BAM810-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam810-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
12.700 ($\frac{1}{2}$)	—	—	—	—	—	BAM 810	—	9.6	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled		
F_w	D	C	Shaft dia. ϕ		Housing bore dia. ϕ		load rating C	load rating C_0	rotational speed ^(*)	inner ring		
mm	mm	mm	h8 Max.	h8 Min.	J7 Max.	J7 Min.	N	N	rpm			
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	15.88 (.625)	1	12.700	12.689	12.700	17.472	17.454	6 350	8 380	30 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173566
Diam. intérieur	12.7 mm
Diam. extérieur	17.46 mm
Épaisseur	15.88 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE