

## Rondelle de butée WS1730-IKO - WS1730-IKO

<https://www.123roulement.ch/accessoire/rondelle/rondelle-butee/ws1730-iko>

**IKO**  
**THRUST BEARINGS**  
Thrust Needle Roller Bearings

| Shaft dia.<br>mm | Identification number        |               |               |               |            |            |               |
|------------------|------------------------------|---------------|---------------|---------------|------------|------------|---------------|
|                  | Thrust needle roller bearing | Mass (Ref.) g | Thrust washer | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 17               | NTB 1730                     | 4.5           | AS 1730       | 3.7           | WS 1730    | GS 1730    | 10.2          |

  

| d  | Boundary dimensions mm |                |   |      |                                   |                | Basic dynamic load rating C N | Basic static load rating C <sub>0</sub> N | Allowable rotational speed <sup>(2)</sup> rpm |        |
|----|------------------------|----------------|---|------|-----------------------------------|----------------|-------------------------------|---|---|--------|
|    | D                      | D <sub>w</sub> | s | B    | r <sub>s</sub> min <sup>(1)</sup> | C <sub>i</sub> |                               |   |   |        |
| 17 | 30                     | 2              | 1 | 2.75 | 0.3                               | 20             | 28                            | 9 320                                     | 32 900  | 11 000 |

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952298863 |
| Diam. intérieur | 17 mm         |
| Diam. extérieur | 30 mm         |
| Épaisseur       | 2.75 mm       |
| Matière         | ACIER         |
| Poids           | 10 g          |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE