

Roulement conique 3190-3126-TIMKEN - 3190-3126-TIMKEN

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/3190-3126-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|--|-------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ Y | Dynamic ⁽³⁾ C ₀₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 30.000 | 72.034 | 30.162 | 9400 | 3.32 | 1400 | 1400 | 1.76 | 10200 | 2190 | |
| 1.1811 | 2.8360 | 1.1875 | 2350 | | 350 | 350 | | 2580 | 3125 | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|-------------------------------|-------------------------------|------|------------------|----------------|----------------|----------------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d ₄ | Max. Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | Cage | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | |
| 29.987 | 29.912 | -18.2 | 3.5 | 38.8 | 44.5 | 2.8 | 67.0 | 61.8 | * | | | | |
| 1.1810 | 0.9275 | -0.40 | 0.14 | 1.50 | 1.75 | 0.11 | 2.64 | 2.40 | * | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952309231 |
| Diam. intérieur | 30 mm |
| Diam. extérieur | 72.03 mm |
| Épaisseur | 30.16 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE